

UFL850-Ta

API 682 4th Edition Category 2 & 3
 Seal type B (Rotating)
 Configuration 2CW-CW (Contacting Wet-Contacting Wet)
 Configuration 3CW-FB (Contacting Wet-Face-to-Back)

Product Description

1. API 682 Category 2 and 3, Type B, Arrangement 2 & 3 seal
2. Dual seal in face-to-back configuration
3. Balanced design
4. Independent of direction of rotation
5. Cartridge construction
6. For plain shafts
7. Rotary metal bellows design
8. Shrink fitted seal rings and solid mating rings

Technical Features

1. Suitable for high and low temperature application
2. Compact design
3. No dynamically loaded O-ring which reduces chances of seal face hang-up.
4. Pumping screw for media with higher viscosity also available
5. Short installation length possible
6. Rugged design for long operating life
7. Bellows design efficiently ensure self-cleaning
8. Bellows design minimizes variation in face load due to shaft expansion or face wear
9. Resistant to abrasive particles in the medium, no shaft or sleeve fretting

Typical Industrial Applications

- API 610/ISO 13709 pumps
- Chemical & Petrochemical industry
- Cold media
- Highly viscous media
- Hot media
- Power plant
- technology
- Refining technology
- Oil and gas industry
- Power plant technology
- LPG plants
- Process pumps

Performance Capabilities

Shaft diameter: $d_1 = 20 \dots 110 \text{ mm}$ (0.79" ... 4.33")
 Pressure: $p = \text{vacuum} \dots 20 \text{ bar}$ (290 PSI)
 Temperature: $t = -40 \text{ }^\circ\text{C} \dots +200 \text{ }^\circ\text{C}$ (-40 °F ... +392 °F)
 Sliding velocity: $v_g \dots 23 \text{ m/s}$ (75 ft/s)

Materials


Seal rings: Blister resistant carbon
 Mating rings: Silicon carbide SSiC (Q1), RBSiC (Q2)
 Bellows: Hastelloy® C-276 (M5),
 option: Inconel® 718 (M6)
 Secondary seals: FKM (V), FFKM (K), EPDM (E), NBR (P)
 Metal parts: CrNiMo steel 316 (G), Hastelloy® C-276 (M5)

Recommended piping plans 2CW-CW

Process side:
 01, 02, 03, 11, 12, 13, 14, 21, 22, 23, 31, 32, 41
 Between seals: 52, 55
 Atmospheric side*: 61, 62, 65A, 65B
 * Throttle bushing on request

Recommended piping plans 3CW-FB

Process side:
 01, 02, 03, 11, 12, 13, 14, 21, 22, 23, 31, 32, 41
 Between seals: 53A, 53B, 53C, 54
 Atmospheric side*: 61, 62, 65A, 65B
 * Throttle bushing on request



Item	Description
1.1.1, 2.1.1	Seal ring with Bellows Unit
1.1.2, 1.3, 2.1.2, 2.3, 4, 6, 9	O-ring
1.1.3, 2.1.3, 14	Set screw
2.1.4	Pumping sleeve
1.2, 2.2	Mating ring
3	Shaft sleeve
5	Gland
7	Multi-flow Distributor
8	Retaining ring
11	Cover
12	HSH cap screw
13	Set ring
15	Setting plate
16	Hexagon screw
F	Flush
LBI	Liquid Buffer/Barrier IN
LBO	Liquid Buffer/Barrier OUT